

### Graffiti


LED spotlight for 3 phase track installations with spot light distribution and stabilized color temperature. Electronic, switchable luminaire. Class I electrical, IP20. Body: die-cast aluminium black micro-textured paint. Reflector: PC sputtered. Spotlight rotatable through 337° and pivotable through 90°. Complete with 4000K LED, maximum efficiency

This article is bulk packed and contains twelve pieces. The article code has to be ordered as a multiple of twelve (12/24/36/48/60...). All the data on the datasheet refer to a single article.

Dimensions: Ø95 x 205 mm  
 Luminaire input power: 27 W  
 Luminaire luminous flux: 3500 lm  
 Luminaire efficacy: 130 lm/W  
 Weight: 0.71 kg



TLG\_GRAF\_F\_3GU\_BK\_ON.jpg



TLG\_GRAF\_M\_3GU.wmf

This product contains a light source of energy efficiency class C.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
 © Thorn Lighting

**Graffiti**

**96108735 GRAFFITI 3600-940HE SWI 3GU SP BK 12X**

**THORN**