

## R2L2

96266202 R2L2 S 36L70 740 NR CL2 GY

### R2L2

A small size LED road lighting lantern with 36 LEDs driven at 700mA with Narrow Road optic. LED driver Programmable. Class II electrical, IP66, IK08. Housing: die-cast aluminium (EN AC-44300), powder coated textured light grey. Enclosure: tempered flat glass. Screws: stainless steel, Ecolubric® treated. Post top (Ø60/76mm, tilted 0°/5°/10°) or lateral (Ø34/42/49/60mm, tilted 0°/-5°/-10°/-15°) mounting. For lateral mounting to Ø34/42mm spigots an adaptor (59005840 R2L2 MA34/42 NPA) should be ordered separately. Complete with 4000K LED.

Dimensions: 655 x 362 x 155 mm  
 Luminaire input power: 75.3 W  
 Luminaire luminous flux: 12110 lm  
 Luminaire efficacy: 161 lm/W  
 Weight: 9.32 kg  
 Scx: 0.05 m<sup>2</sup>



TLG\_R2L2\_F\_SPDB.jpg



TLG\_R2L2\_M\_LDS.wmf

This product contains a light source of energy efficiency class E.

**R2L2**

**96266202 R2L2 S 36L70 740 NR CL2 GY**

**THORN**