

Vioo

96271767 VIOO 1L120 740 LGRY

THORN


Vioo

Small LED floodlight for window surround illumination. 1 LED driven at a constant 1.2A. Body: die-cast aluminium (AB47100) with high corrosion resistance, painted Light grey. Front lens: polycarbonate. Class I electrical, IP65, IK10. Pre-wired with 1,5m H05-RNF cable. Complete with 4000K LED

Dimensions: 150 x 90 x 40 mm
Luminaire input power: 4.7 W
Luminaire luminous flux: 200 lm
Luminaire efficacy: 43 lm/W
Weight: 0.71 kg



TLG_VIOO_F_PDB.jpg



TLG_VIOO_M_LD1.wmf

This product contains a light source of energy efficiency class F.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

Vioo

96271767 VIOO 1L120 740 LGRY

THORN