

Omega Circular

96627771 OMEGA C LED2800-830 HF R400

THORN


Omega Circular

A versatile, circular edge lit panel for recessed mounting in a $\text{\O}200\text{mm}$ cutout. Electronic, fixed output control gear. Class I electrical, IP20. Body: aluminium and steel, white (RAL 9016). Diffuser: acrylic opal. Complete with 3000K LED.

Dimensions: $\text{\O}400 \times 55 \text{ mm}$
Luminaire input power: 33 W
Luminaire luminous flux: 2649 lm
Luminaire efficacy: 80 lm/W
Weight: 3.3 kg



TLG_OMGC_F_PDB.jpg



TLG_OMGC_M_2800.wmf

This product contains a light source of energy efficiency class E.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C .

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

Omega Circular

96627771 OMEGA C LED2800-830 HF R400

THORN