

Arena Symphony

96645156 ARENA LED6500-840 HFSX TW WL6 EFL

THORN

Arena Symphony

A suspended architectural raft, incorporating a direct/indirect LED luminaire and sensor unit (daylight / presence / remote) control, connected to the DALI bus. Electronic, DALI dimmable control gear. Class I electrical, IP20. Raft and luminaire frame: aluminium. Optic: flat acrylic. Supplied with a 6 pole Wieland plug on 3.4m of 6 core cable and a panel mounted 6 pole Wieland socket for through wiring. Supplied with suspension wires. Complete with 4000K LED.

Dimensions: 2200 x 850 x 100 mm

Luminaire input power: 55.5 W


Luminaire luminous flux: 6300 lm

Luminaire efficacy: 114 lm/W

Weight: 23.7 kg



TLG_ARNS_F_EFL.jpg



TLG_ARNS_M_LD1.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting