

# Arena Symphony

96645141 ARENA LED6500-840 HFSX E3 TW WL6 EDP

THORN

## Arena Symphony

A suspended architectural raft, incorporating a direct/indirect LED luminaire and sensor unit (daylight / presence / remote) control, connected to the DALI bus. Electronic, DALI dimmable control gear with 3 hour, manual test, emergency lighting circuit. Class I electrical, IP20. Raft and luminaire frame: aluminium. Optic: curved acrylic. Supplied with a 6 pole Wieland plug on 3.4m of 6 core cable and a panel mounted 6 pole Wieland socket for through wiring. Supplied with suspension wires. Complete with 4000K LED.

Dimensions: 2200 x 850 x 135 mm

Luminaire input power: 55.5 W


Luminaire luminous flux: 6500 lm

Luminaire efficacy: 117 lm/W

Weight: 23.2 kg



TLG\_ARNS\_F\_EDP.jpg



TLG\_ARNS\_M\_LD2.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

# Arena Symphony

96645141 ARENA LED6500-840 HFSX E3 TW WL6 EDP

THORN