

# Areapak Pro

22664348 APP L 96L70 L840 S45 CL1 100H

THORN

## Areapak Pro

A versatile, large sized LED area floodlight with fixed output control gear driving 96 LEDs at 700mA with symmetrical 45° distribution. Class I electrical, IP66, IK08. Body: die-cast aluminium, painted light grey (RAL 9006). Heatsink: die-cast aluminium, painted dark sandy grey (RAL 7043). Frame and stirrup: hot-dip galvanised steel. Enclosure: 5mm toughened glass. Screws: stainless steel. Reversible mounting stirrup supplied, can be fitted with one Ø22mm, two Ø15mm and/or two Ø12mm holes. Complete with 4000K LED, Colour Rendering Index min.: 80.

Dimensions: 616 x 492 x 226 mm  
Luminaire input power: 211 W  
Luminaire luminous flux: 24072 lm  
Luminaire efficacy: 114 lm/W  
Weight: 19.8 kg  
Scx: 0.073 m<sup>2</sup>



TLG\_ARPP\_F\_LPDB.jpg

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting