

IQ Wave SP

96629305 IQ SURF L LED6700-840 HFSX

THORN

IQ Wave SP

A lightweight, Surface mounted, LED luminaire with MV Tech optic. Electronic, DALI dimmable control gear. Equipped with daylight and presence detection for dimming control. Class I electrical, IP40, IK05. Body, diffuser, frame and endcaps: polycarbonate finished in white (close to RAL9016). Gear tray: pre-coated white steel. Complete with 4000K LED


Dimensions: 1465 x 210 x 70 mm

Luminaire input power: 61 W


Luminaire luminous flux: 6700 lm

Luminaire efficacy: 110 lm/W

weight: 5.1 kg



TLG_IQSU_F_SUS_BELOW_SENS.jpg



TLG_IQSU_M_SURS.wmf

This product contains a light source of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

IQ Wave SP

96629305 IQ SURF L LED6700-840 HFSX

THORN