

R2L2

96275563 R2L2 M 60L35-740 NR BS 3550 CL2 GY


R2L2

A medium size LED road lighting lantern with 60 LEDs driven at 350mA with Narrow Road optic. LED driver Programmable. Class II electrical, IP66, IK08. Housing: die-cast aluminium, powder coated textured light grey. Enclosure: tempered flat glass. Screws: stainless steel, Ecolubric® treated. Post top (Ø60/76mm, tilted 0°/5°/10°) or lateral (Ø34/42/49/60mm, tilted 0°/-5°/-10°/-15°) mounting. For lateral mounting to Ø34/42mm spigots an adaptor (59005840 R2L2 MA34/42 NPA) should be ordered separately. Equipped with 50% power reduction circuit, effective 3 hours before and 5 hours after a calculated midnight. It can be deactivated at installation with an easily accessible internal switch. Complete with 4000K LED.

Dimensions: 880 x 370 x 155 mm
 Luminaire input power: 62.5 W
 Luminaire luminous flux: 10606 lm
 Luminaire efficacy: 170 lm/W
 Weight: 13.4 kg
 Scx: 0.06 m²



TLG_R2L2_F_MPDB.jpg



TLG_R2L2_M_LDM.wmf

This product contains light sources of energy efficiency classes D, E.

R2L2

96275563 R2L2 M 60L35-740 NR BS 3550 CL2 GY

THORN