## Raze Architectural



## 96632096 RAA S 1L35-830 HFX/R 6K MSF ANT

## Raze Architectural

A compact, Surface mounted, LED wall grazer, incorporating Thorn's Flat beam® technology. 1 LED driven at 350mA. Remote DALI dimmable LED driver included. Class III electrical, IP66, IK08. Housing: die-cast aluminium (EN44300, compatible with seaside installation), powder coated, textured anthracite (close to RAL7043). Bowl: UV stablised polycarbonate, frosted. Fasteners: stainless steel. Complete with 3000K LED.

S version driver capable of supplying up to three luminaires.

MSF variant with adjustable tilt up to ±15°.

MWA variant flush mounting.


6kV surge protection as standard. Pre-wired with 2m cable.

Dimensions: 109 x 110 x 72 mm Luminaire input power: 6 W Luminaire luminous flux: 350 lm Luminaire efficacy: 58 lm/W

Weight: 0.84 kg



TLG RAZA F S MSF PDB.jpg



TLG\_RAZA\_M\_S\_MSF.wmf

This product contains a light source of energy efficiency class F.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

## Raze Architectural 96632096 RAA S 1L35-830 HFX/R 6K MSF ANT

