

# Durolight

96633054 DUROLIGHT-R 5300-840 HFIX L1525

THORN

## Durolight

Anti-vandal Recessed LED luminaire. Electronic, DALI dimmable control gear. IP65, IK10, Class I electrical. Body: 2mm sheet steel painted white (close to RAL9016). Gasket: non-ageing polyurethane foam. Diffuser: 3mm thick polycarbonate with outstanding impact resistance, connected and secured with tamper-resistant stainless steel twin hole screws to the body. Complete with 4000K LED

Dimensions: 1525 x 300 x 115 mm

Luminaire input power: 46.7 W


Luminaire luminous flux: 5246 lm

Luminaire efficacy: 112 lm/W

Weight: 17 kg



TLG\_DURO\_F\_MRE.jpg



TLG\_DURO\_M\_LDR.wmf

This product contains a light source of energy efficiency class C.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting