

# Durolight

96633065 <DUROLIGHT-S 4100-840 HFIX L1350

THORN

## Durolight

Anti-vandal Surface mounted LED luminaire. Electronic, DALI dimmable control gear. IP65, IK10, Class I electrical. Body: 2mm sheet steel painted white (close to RAL9016). Gasket: non-ageing polyurethane foam. Diffuser: 3mm thick polycarbonate with outstanding impact resistance, connected and secured with tamper-resistant stainless steel twin hole screws to the body. Complete with 4000K LED

Dimensions: 1350 x 290 x 66 mm

Luminaire input power: 38 W


Luminaire luminous flux: 4100 lm

Luminaire efficacy: 108 lm/W

Weight: 15 kg



TLG\_DURO\_F\_MCE.jpg



TLG\_DURO\_M\_LDS.wmf

This product contains a light source of energy efficiency class C.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

**Durolight**

**96633065 <DUROLIGHT-S 4100-840 HFIX L1350**

**THORN**