

## 96634895 CETUS3 M LCS HF RWH

### Cetus


A low height, recessed LED downlight. Suitable for ceiling cut-outs Ø145-180 mm for easy refurbishments or fast initial installations. Remote, pluggable, Fixed output LED driver. Loop in - loop out possible. Body: die-cast aluminium for thermal management. Diffuser: polycarbonate, smooth reflector in white finish with wide beam. Reflector and trim: high quality, highly reflective polycarbonate. Class II electrical, IP44\_IP20. Spring clips suitable for ceiling thicknesses from 1 to 35 mm.

Equipped with LCS technology, with two lumen outputs (2000lm and 3400lm) and three colour temperatures (3000K, 3500K and 4000K) selectable from below by a rotary switch. Pre-set to 4000K, high luminous flux.

Dimensions: Ø195 x 100 mm  
 Luminaire input power: 25.4 W  
 Luminaire luminous flux: 3221 lm  
 Luminaire efficacy: 127 lm/W  
 Weight: 0.58 kg



TLG\_CTU3\_F\_M\_LED\_RWH\_Persp.jpg



TLG\_CTU3\_M\_HFM.wmf

This product contains a light source of energy efficiency class D.

**Cetus**

**96634895 CETUS3 M LCS HF RWH**

**THORN**