

## Punch

**96635396 <PUNCH 3 LRO MSP 6600-940 L15 HFIX SWD**

### Punch

A slim, suspended luminaire with direct/indirect distribution. DALI dimmable Electronic, . Equipped with pull cord dimming switch. Body: sheet steel, powder coated white (close to RAL9016). Endcaps: sheet steel powder coated white (close to RAL9016). Light guided via backlit multilayer PMMA LRO luminance reducing optic with UGR <19, closed optical system to prevent damage from electrostatic discharge, ideal for schools and offices. Class I electrical, IP20, Impact strength: IK03. Electrical connection via pre-installed power cord (2.5m). Complete with 4000K LED.

Y-Suspension connector included - Suspension cord with ceiling rose to be ordered separately (22171581).

Dimensions: 1542 x 162 x 50 mm

Luminaire input power: 63.4 W


Luminaire luminous flux: 6789 lm

Luminaire efficacy: 107 lm/W

Weight: 6.5 kg



TLG\_PNCH\_F\_LRO\_suspended\_on\_PDB.jpg



TLG\_PNC3\_M\_PLEXD.wmf

This product contains light sources of energy efficiency class D.

**Punch**

**96635396 <PUNCH 3 LRO MSP 6600-940 L15 HFIX SWD**

**THORN**