

## Punch

### 96636038 PUNCH 3 LRO MSC 3800-940 L15 HF

#### Punch


A slim, surface mounted luminaire with direct distribution. fixed output control gear Electronic,. Body: sheet steel, powder coated white (close to RAL9016). Endcaps: sheet steel powder coated white (close to RAL9016). Light guided via backlit multilayer PMMA LRO luminance reducing optic with UGR <19, closed optical system to prevent damage from electrostatic discharge, ideal for schools and offices. Class I electrical, IP20, Impact strength: IK03. Electrical connection via piano key terminal block. Complete with 4000K LED.

Can be used as a suspended direct only luminaire when combined with Y-Suspension connector and suspension kit (to be ordered separately 22171581 & 22171349).

Dimensions: 1542 x 162 x 50 mm  
 Luminaire input power: 29.7 W  
 Luminaire luminous flux: 3705 lm  
 Luminaire efficacy: 125 lm/W  
 Weight: 3.8 kg



TLG\_PNCH\_F\_LRO\_surface\_on\_PDB.jpg



TLG\_PNC3\_M\_PLEXD.wmf

This product contains light sources of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

# Punch

96636038 PUNCH 3 LRO MSC 3800-940 L15 HF

THORN